Fully / Semi Synthetic

Kixx Ultra 4T Scooter SN

Top grade engine oil, the perfect fit for four-stroke scooters

API SN
JASO MB RECOMMENDED



DESCRIPTION

Kixx Ultra 4T Scooter SN is formulated from Synthetic Technology meeting the requirement of current advanced top-tier engine oil grade of API SN. It is optimized to provide complete scooter engine oil performance especially for fuel efficiency, reducing friction loss and durability.

APPLICATIONS

- All gasoline fueled vehicles
- High performance cars equipped with DOHC, EFI and VVT
- Four-stroke gasoline engines in motorcycles
- Sports Vehicles

PERFORMANCE STANDARDS

- API SN
- 5W-40 / 10W-40: JASO MB Recommended

CUSTOMER BENEFITS

Fuel economy

The wide temperature range capability of the synthetic technology base fluid ensures correct oil viscosity which reduces friction at start-up, and provides maximum lubrification during high temperature operation.

Engine power and maintainability

A reduction in the piston blow-by gas coupled with the oil's antisludge characteristics help maintain engine power and cleanliness, which in turn extends the engine's service life.

Oil drainage interval

Excellent oxidation resistance and low volatility will extend oil drainage interval.

All-temperature wear resistance

Advanced non-conventional base oil formula coupled with high performance additive systems and leading edge viscosity index improver delivers excellent shear stability and maximum wear protection in high speed, high temperature driving conditions as well as a rapid, highly effective oil film protection. It also provides component wear resistance during very low temperature cold starts.

| KEY PROPERTIES | Fully Synthetic | Semi Synthetic |
|---|---------------------------|-------------------|
| SAE Viscosity | 5W-40 | 10W-40 |
| Density, kg/L @15°C | 0.849 | 0.861 |
| Kinematic Viscosity, mm ² /s @ 40°C | 83.9 | 104.8 |
| Kinematic Viscosity, mm ² /s @ 100°C | 14.4 | 15.7 |
| Viscosity Index | 178 | 159 |
| Pour Point °C | -42 | -42 |
| Flash Point °C | 222 | 220 |
| Package (Liters) | 0.8,1,200 | 0.8,1,200 |